

PRODUCT Nº:1040

## TECMA PAINT® METALIZADOR-Z FAST METAL PROTECTION

### DESCRIPTION

Anticorrosive paint in aerosol can, designed for covering metal areas which have lost galvanized and for little touches on metal elements which have to be protected quickly. Its formulation, thanks to the anticorrosive metal particles, assures antioxidising protection on those areas which have been left unprotected due to welding, shocks, scratches, etc.

### APPLICATION FIELD

**TECMA PAINT® METALIZADOR** is recommended for repairing galvanized elements and protecting steel surfaces where the job has to be done quickly. Its use is absolutely necessary in locksmithery, welding workshops and galvanized elements assembling, plumbing, cooling and heating elements assembling, etc.

### SURFACE CONDITIONING

Surfaces must be dry and free from grease, oil, dust or any other pollutant. Surfaces with rust remains have to be deoxidized by mechanical means until removing every rust remaining.

In order to enhance adherence, the metal surface has to be sanded or brushed with a metal brush in order to provide the surface to be painted with roughness.

### CHARACTERISTICS

Appearance: Metal

Drying time at 20 °C and 55% R.H. : Touch 5 minutes, repainted 15 minutes.

Application : Spraying

Adherence : 100% on great variety of different metal surfaces which are well conditioned.

### METHOD OF USE

Shake the can thoroughly. Spray on the area to be covered, keeping the can vertical and at about 20-30 cm from the surface. Make the application trying not to charge the area with too much product and uniformly spreading the product all over the surface to be protected.

Once the first coat is dry, it's possible to apply a second one.

After applying, turn the can upside down in order to clean the sprayer.

## SPECIAL RECOMMENDATIONS

- Apply with good ventilation.
- Never apply on greasy, dirty or damp surfaces.
- Do not apply with temperatures below 5 °C or with relative humidity above 85%.
- When applying on other paints, verify compatibility and adherence with the existing paint.
- Do not apply on hot surfaces.

## PACKAGING AND STORAGE

**TECMA PAINT® METALIZADOR-Z** is supplied in 600 cc aerosol cans. Keep in a cool place protected from sunlight and from temperatures above 50 °C.

## ADVANTAGES

- Quick and efficient protection for metal surfaces.
  - Quick drying, reducing dead times
  - Great yield per can

ED. 1995/1