

PRODUCT No.: 1.412

TELA DE ARMAR REINFORCEMENT

DESCRIPTION:

Resistant woven glass fibre. Due to its special constitution, it's easy to be included in **IMPERMEABILIZANTE E-88**, **TECMA ELAST V-97** and **TECMA IMPERAL P-91** or **P-98**. With that, it's possible to get more toughness in the waterproofing, especially on areas with cracks or extension joints.

RANGE OF APPLICATION:

The **TELA DE ARMAR** is recommended when reinforcing waterproofing in areas with cracks and expansion joints in terraces, roofs and covers which are to be waterproofed with **IMPERMEABILIZANTE E-88**, **TECMA ELAST V-97** or **TECMA IMPERAL P-91** or **P-98**.

It's recommended to be placed on singular elements in terraces or roofs, such as drains and in unions between floor and walls.

It's also used for reinforcing the waterproofing of eaves gutters and for continuous reinforcement in terraces to be waterproofed.

METHOD OF USE:

The **TELA DE ARMAR** must be placed immediately after applying the first coat of the waterproofing material. Press afterwards with the roller so that the fabric gets fixed. Once the first coat is dry, keep applying the rest of the coats.

The overlapping of the fabric must be made in the sense of the water fall and overlapping about 15 cm. In unions between floor and wall, the fabric will go up the wall about 25 cm, just as the waterproofing which is being applied.

For drains, place a piece of fabric on the drain mouth so there are about 15 cm between the drain edge and the fabric. Apply a first coat with the waterproofing material. When it's still damp, make two cuts in the fabric on the drain and introduce the borders. Press the fabric inside with the roller in order to let it get fixed to the inside walls of the drain. Apply afterwards the rest of the waterproofing material as usual.

PACKAGING:

The product is supplied in continuous rolls with 1 m width.

ED.2000/1