

PRODUCT Nº: 1.516

PRIMER 1833 PRIMER FOR POLYURETHANE SEALANTS

DESCRIPTION

Penetrating and sealing primer for porous surfaces to be used with our polyurethane sealants **SATECMAELASTIC PM 33** and **SATECMAELASTIC P-400**. Its use allows improving adherence on most of the materials such as concrete, marble, artificial and natural stone, granite, mortar, etc.

FIELD OF APPLICATION

It's used as sealing primer for porous surfaces on which there can be migration of the mastic. It's recommended in cases when it's necessary to improve adherence due to the conditions to which the sealant it's going to be submitted, especially in conditions of constant immersion.

It is also recommended when sealing materials with possible disintegration.

CHARACTERISTICS

Appearance:	Liquid
Drying time at 20 °C and 55% R.H.:	The application of the sealant will be done 30 or 60 minutes after the primer has been applied
Theoretical yield:	50-100 g/m ² depending on the porosity

SURFACE CONDITIONING

Surfaces should be perfectly dry and free from grease, dust or any other pollutant.

METHOD OF USE

Apply with brush over the whole surface to be sealed. Pay special attention to the inside of the joint in order to assure correct application. After 30-60 minutes, it'll be possible to apply the chosen sealant.

SPECIAL RECOMMENDATIONS

- Never apply with temperatures below 5 °C
- Never apply when relative humidity is above 80% or when the temperature of the support is less than 3 °C above dew point.
- Before applying the product, check the absence of dampness in the support.
- After using the product, the container should be tightly closed.

PACKAGING AND STORAGE

The product is supplied in 0,5 and 1 litre containers. It should be kept in its original container, tightly closed. In these conditions, it can be stored for at least a year.

ED. 2000/1