

PRODUCT No.: 1709-B.
1710-G.
1711-R.
1712.V.

TECMA PAINT® AS

ACRYLIC PAINT FOR FLOORS

DESCRIPTION:

Coating formulated based on acrylic copolymers in water dispersion and weather resistant pigments.

TECMA PAINT® AS has water and alkali resistance. It's easy to apply and dries quickly.

CHARACTERISTICS:

Density	:	1,35 ± 0,03 kg./l.
Viscosity	:	100 ± 5 KU
Drying time at 20°C - 55% R.H.	:	Touch : 35/45 minutes Hard: 2 hours Repainted: 4 - 6 hours
Application	:	Brush or roller
Solvent	:	Water
Appearance	:	Satin
Colours	:	White, Grey, Ochre, Green (according to our colour chart)
Recommended No. of coats	:	Two
Theoretical Yield	:	5 m ² / kg. at 50 microns

The real yield will depend on the porosity and roughness of the support, on the thickness applied, on the paint dilution, on the method of application, on the weather conditions, etc.

FIELD OF APPLICATION:

TECMA PAINT® AS is recommended for painting sports centres, industrial premises floors, which are not submitted to great abrasions or chemical aggressions, warehouses floors and in general, all those floors made of cement or concrete which do not require great mechanical or chemical needs.

TECMA PAINT® AS is a good protection for concrete against carbonatation, thus being useful in protecting outside façades and structures made of mortar and concrete.

SURFACE CONDITIONING:

Surfaces must be dry and free from oil, grease or any other pollutant. Little porous and smooth surfaces should be roughened using mechanical means or chemical attack with our **DESCA 2F**, rinsing afterwards with plenty of water until completely removing the product. Make sure that after chemically treating the surface, this gets not disgregated or loses coherence due to the existence of dissolved salts in the treated surface.

MEHTOD OF USE:

Once the surface is conditioned, apply the first coat diluted with 15-20 % water, in order to let the paint penetrate in the pores of the support and get a good fixing. After 4 – 6 hours, apply the second coat without or with minimum dilution.

SPECIAL RECOMMENDATIONS:

- Do not apply with temperatures below 10 °C, or relative humidity above 85%
- Do not apply when rain is expected before the paint is dry.
- When painting sport trucks with discontinuous pavement, the yields would be reduced due to the porosity of the pavement and since it's constituted of great amount of aggregate particles which have several facets which have to be covered in order to get uniform application.

PACKAGING:

In 10 and 25 kg varnished metal drums.

ADVANTAGES

- **Easy application and repainting.**
- **Excellent weather resistance.**
- **Possibility of antiskid finish.**

TECMA PAINT® AS is a trade mark owned by **Industrias Químicas Satecma® S.A.**

ED.1994/1