

PRODUCT No.: 1.714

TECMA PAINT® BTA

ASPHALTIC PAINT

CHARACTERISTICS:

Coating based on asphalt in solution, designed for protection against dampness in walls made of cement or concrete, metal plates, tanks, metal elements, etc., which are to be buried.

PROPERTIES:

Thanks to its low viscosity, this coating can be applied with brush, roller or airless, providing a continuous surface.

The application can be made by unqualified staff.

It's used cold, not needing to be heated.

Has good properties of temperature resistance, bearing temperatures up to 60° C.

Drying time is 24 hours.

Yield: 4 - 5m²/Lt.

Diluent: **TECMA SOL BTA.**

SURFACE CONDITIONING:

Surfaces must be dry and free from grease, oil, dust sand or any other pollutant.

Loose grout must be removed.

In steel surfaces, it's recommended to provide the support with roughness by abrasive blasting, mechanical brush, sanding, etc., thus enhancing adherence to the support.

METHOD OF USE:

In little porous supports, dilute the first coat with up to 15% of our **TECMA SOL BTA** in order to allow the penetration of the coating in the support. Once the first coat is dry after 24 hours, apply the second one, without dilution.

SPECIAL RECOMMENDATIONS:

- Do not apply with fog or drizzle.
- Do not apply with temperatures below 5° C.

PRECAUTIONS:

- Keep suitable ventilation while applying.
- Do not expose to flames or heat sources. The liquid product is flammable.
- When applying with gun, wear suitable masks.
- Avoid contact with skin or eyes.

PACKAGING:

In 25 litre metal drums.

ED.1999/1