

PRODUCT No.: 1730

## TECMA PAINT® OPS

### SIGNALLING PAINT FOR VIALS

#### DESCRIPTION

Paint based on modified chlorinated rubber, designed for painting horizontal signalling in roads, streets, pavements, etc.

#### TECHNICAL DATA:

Nº of components	:	One
Colours	:	White and Yellow
Appearance	:	Matt
Yield	:	3 - 7 m <sup>2</sup> /kg. depending on the surface roughness and the thickness
Drying times at 20° C - 55% R.H.	:	Touch 10 minutes Repainted 40 minutes Possible traffic 1 hour
Application	:	Brush, roller or gun.
Thinner	:	<b>TECMA SOL C</b>

#### SURFACE CONDITIONING:

Surfaces should be dry and free from grease, oil, sand and dust or any other pollutant. In polished concrete surfaces, it's recommended to roughen by mechanical means or by attacking with our **DESCA 2F**, rinsing afterwards with plenty of water in order to remove excess of product.

#### METHOD OF USE

Shake the container before using. In order to apply on concrete or cement, the first coat should be diluted with 10-15 % of **TECMASOL C** in order to allow product penetration in the support.

On asphalt, it can be used as it's supplied.

In order to apply the following coats, respect repainting periods. The paint needs no dilution.

## SPECIAL RECOMMENDATIONS:

- Apply with good ventilation.
- Do not expose to flame or heat sources. The liquid product is flammable.
- Avoid contact with skin or eyes.

## PACKAGING:

In 15 and 30 kg metal drums.

## ADVANTAGES

- Short dead times.
- Quick marking of signalling.
- Good acceptance of glass spheres, getting high reflection.

TECMA PAINT® OPS is a trade mark owned by Industrias Químicas Satecma®,S.A.

ED.1994/1