

PRODUCT Nº.: 1771

TECMASOL AP GRAFFITI CLEANER

DESCRIPTION:

Special cleaner for the graffiti made on our protection varnish TECMA PAINT ANTIGRAFFITI. Its use as graffiti cleaner allows total removing of the graffiti in a quick and simple process.

CHARACTERISTICS

Appearance	: Clear liquid
Colour	: Colourless
Density, 20°C	: 0,863 ± 0,005 gr/c.c.
Refractive index 25°C	: 1,4705 ± 0,0015
Contents in chlorinated compounds	: None
Contents in acids and alkalis	: None

FIELD OF APPLICATION:

TECMASOL AP is used to remove graffiti made with aerosol, soft pens, brush, etc., which have been made on our protection varnish TECMA PAINT ANTIGRAFFITI.

METHOD OF USE:

Wet the graffiti with **TECMASOL AP** with the help of a triggersprayer or a damp cloth on the graffiti. Let work for a few seconds and softly rub the surface with a cloth until removing all the rest of paint or ink. In case of having old graffiti, if they can not be easily removed, it'll be possible to use a soft brush (as the ones used for cleaning hands) rubbing on the graffiti after soaking it with **TECMASOL AP**.

SPECIAL RECOMMENDATIONS:

When removing the graffiti, never use abrasive materials or tools which could scratch or damage the antigraffiti protection.

The best results are achieved with temperatures between 15 and 25 °C.

PRECAUTIONS:

TECMASOL AP is a flammable product so it should not be handled near heat, flame or ignition sources.

Try to have good ventilation while handling.

ED.2001/2