

PRODUCT N°: 3.189

## DECAPA-SCM FLUIDO

### FLUID STRIPPER OF PAINT, VARNISH AND GRAFFITI

#### FEATURES:

**DECAPA-SCM** is a stripper product free of chlorinated compounds, in liquid form and characteristic odor. Because of its special composition removes all types of paint applied on any media such as concrete, wood, metal plate, etc., producing a softening and subsequent blistering in alkyd paints, epoxy, polyurethane, etc.. and dissolution of acrylic, vinyl, chlorinated rubber paints, etc., allowing complete removal of coatings, however old it may be.

Depending on the type, age of the painting, the thickness of the layer required to be stripped and temperature, the product will perform in a few minutes or in several hours.

#### INSTRUCTIONS:

**DECAPA-SCM** can be used as presented to or diluted in water at the time of application. Depending on the type and thickness of the paint layer, can be eliminated even with a dilution in water of 50%. For paints of film formation by chemical reaction, epoxies, polyurethanes, application of the pure product is recommended. Layered acrylic paints, synthetic enamels, chlorinated rubber, vinyl, the product can be diluted with water in the proper dilution that a prior testing indicate.

Apply to the surface to be stripped an even layer, 1-2 mm thick of **DECAPA-SCM** by brush or roller made of resistant material to the product and leave for 5 minutes to several hours depending on the type of paint, thickness and ambient temperature (at lower temperatures, the necessary action time increases). A softening and blistering of the paint will be produced, or a solution thereof, and can be removed by scrapers or water pressure.

Where stripping vertical surfaces, we recommend the use of our product **DECAPA GEL-SCM**, to prevent sagging of the product and improve contact times paint-stripper.

**DECAPA-SCM** may be used, in some types of applications, by immersion bath for the stripping of small objects. It is recommended to use a sealable container to prevent evaporation of the product.

When **DECAPA-SCM** is used in enclosed or poorly ventilated places it is necessary to have forced ventilation to prevent accumulation of vapors. The product is flammable and should therefore be kept the necessary preventive measures to manage this type of product.

#### PRECAUTIONS:

Highly flammable. Do not apply near open flame, sources of ignition, electrical contacts, etc.

#### PRESENTATION:

**DECAPA-SCM** is packaged in non-returnable containers of 5, 10 and 25 kg net.

### BENEFITS

\*\*\* GOOD POWER STRIPPER.

\*\*\* CAN BE APPLIED ON ALL TYPES OF PAINTS.

\*\*\* FREE FROM HARMFUL CHLORINE COMPOUNDS.

\*\* The information contained in this sheet, as well as our recommendations, both verbal and written or by tests conducted in our internal laboratories or in external laboratories, are given in good faith based on our experience and test results without that serve as a guarantee. Our recommendations are not exempt from the obligation to learn more about the implementation of the product to be used prior to their use and take pre-tests if there is doubt about the suitability of these for any work or application. The application, use and handling of our products are beyond our control and therefore under the responsibility of the applicator. It will be therefore responsibility of the person who makes use of the product without the observance of the instructions given here \*\*

ED.2012/1