

PRODUCT Nº: 3.190

## DECAPA-SCM GEL

VISCOUS GEL STRIPPER FOR PAINT, VARNISH AND GRAFFITI

### FEATURES:

**DECAPA-SCM GEL** is a stripper product free of chlorine compounds, as a viscous gel designed for application on vertical and horizontal surfaces. Due to its special composition it removes all types of paint applied on any kind of support such as concrete, wood, sheet metal, etc., producing a softening and subsequent blistering in alkyd, epoxi, polyurethane paints and dissolution of acrylic, vinyl, chlorinated rubber paints, allowing complete removal of coatings, however old they may be.

Depending on the type, age of the painting, thickness of the layer required to be stripped and temperature, the product will perform in a few minutes or in several hours.

### INSTRUCTIONS:

**DECAPA-SCM GEL** can be used as it is presented or diluted in water at the time of the application. The dilution will reduce the viscosity of the product and the layer can collapse if applied on vertical surfaces. Depending on the type and thickness of the paint coating, it can be eliminated even with a dilution in water of 50%. For paints of film formation by chemical reaction, epoxies, polyurethanes... application of the pure product is recommended. For coatings of acrylic paints, synthetic enamels, chlorinated rubber, vinyl... the product can be diluted in water in the proper dilution indicated by a prior testing.

Apply to the surface to be stripped an uniform layer of 1-2 mm of **DECAPA-SCM GEL** by brush or roller of a material resistant to the product and leave for 5 minutes to several hours depending on the type of paint, thickness and ambient temperature (at lower temperatures the necessary action time increases). Softening and blistering of the paint will occur, or a solution thereof that could be removed with spatulas or water under pressure.

In some cases where the thickness of the paint layer to eliminate is high, the treatment should be repeated until total elimination.

When **DECAPA-SCM GEL** is used in enclosed or poorly ventilated places it is necessary to have forced ventilation to prevent accumulation of vapors. The product is flammable and should therefore be kept preventive measures necessary to manage this type of products.

## PRECAUTIONS:

Highly flammable. Do not apply near open flame, sources of ignition, electrical contacts, etc.

## PRESENTATION:

**DECAPA-SCM GEL** is packaged in non-returnable containers of 5, 10 and 25 kg net.

## BENEFITS

\*\*\* GOOD STRIPPING POWER.

\*\*\* APPLICABLE ON ALL TYPES OF PAINTS.

\*\*\* FREE OF HARMFUL CHLORINATED COMPOUNDS.

\*\* The information contained in this sheet, as well as our recommendations, both verbal and written or by tests conducted in our internal laboratories or in external laboratories, are given in good faith based on our experience and test results without that serve as a guarantee. Our recommendations are not exempt from the obligation to learn more about the implementation of the product to be used prior to their use and take pre-tests if there is doubt about the suitability of these for any work or application. The application, use and handling of our products are beyond our control and therefore under the responsibility of the applicator. It will be therefore responsibility of the person who makes use of the product without the observance of the instructions given here \*\*

ED.2012/1