

PRODUCT Nº.: 4002

## DECAPA GRAFFIT GRAFFITI REMOVER PASTE

### DESCRIPTION:

Special remover for graffiti made with felt-tip pens, to be used on polished mineral surfaces, such as marble or granite. The product is supplied with two components: one of them is a liquid which has been formulated based on strongly oxidizing and greatly humidifying agents, and the other one is a powder with a high specific surface, which has been chemically activated to offer great absorption in order to remove ink and paint remains.

The ideal mixture proportion is: 87 parts (weight) component A and 13 parts weight) component B.

### CHARACTERISTICS:

Great fixing capacity on vertical surfaces without falling.

Exhaustive removing of graffiti made with felt-tip pens.

Easy to apply with slice or any other tool which allows the spreading of a coat of product on the surface.

Great yield; depending on the surface roughness, the yield can be estimated in 1 kg/m<sup>2</sup> with 1 mm film thickness.

### METHOD OF USE:

The product is supplied in the correct doses to make the mixture: 87 parts component A and 13 parts component B. With this proportion it's possible to get a paste which can be handled and is able to adhere without falling to any type of surface. It would be possible to slightly change this proportion, depending on the surface to be treated.

Pour the component A, liquid, over component B, solid, and stir for a few minutes until getting a homogeneous paste with no lumps in it. When preparing quantities different from the ones in the containers, put component B in a container and separately add component A until getting the required paste.

Adding too much or too little quantity of one of the components does not affect the efficiency of the product but it does affect the consistency of the paste which could turn out to be too fluid and little adhesive or too thick and difficult to handle.

Apply the paste on the graffiti with a slice or any other tool, so that it forms a 2 mm film on it. Cover the application with a black plastic (opaque if not black), fixing it with adhesive tape to the surface, trying to make it as tight as possible in order to make it more efficient.

Wait for 24-72 hours, depending on the penetration of the graffiti, take the plastic off and remove the product and its remains with a slice and a strong brush, rinsing afterwards with water the whole surface.

## **SPECIAL RECOMMENDATIONS:**

The mixture of the two components can be kept in tightly closed containers for a few days. Before using the mixture again, stir thoroughly in order to make it homogeneous. For small application, it's recommended to prepare only the necessary amount. Never apply on metal, painted or lacquered surfaces. Do not apply very thin coats, since it would make the removing quite difficult.

## **PACKAGING:**

DECAPA GRAFITT is supplied in 5 kg sets: component A in 4,35 kg plastic containers and component B in 0,65 kg plastic buckets.

## **PRECAUTIONS:**

When handling the product, it's recommended to wear rubber gloves and clothe and eye protection which is suitable for handling chemicals. Avoid eye and skin contact. Should the product be in contact with the eyes, wash immediately with plenty of water (keeping the eyes open) for several minutes. Should the product be in contact with the skin, wash with plenty of water without rubbing.

ED. 2002/2