

PRODUCT Nº .:4115

TECMASIL PRIMER

SEALING PRIMER FOR SILICATE PAINTS

DESCRIPTION:

TECMASIL PRIMER is a penetrating and sealing primer for porous surfaces, which controls absorption and reinforces the surface of the substrates which are to be painted with silicate based paints, such as **TECMA PAINT SILICATOS**.

CHARACTERISTICS:

Nature	: Silicate
Adherence	: Perfect on a great range of supports
Dilutant	: Water
Recommended yield	: 8 - 10 m ² /l depending on the porosity
Application	: Brush or roller
Drying time at 20°C - 55% R H	: Touch – 4 hours / Repainting – 24 hours

PROPERTIES:

Excellent adherence on a great range of supports, such as mortars, brick, fiber-cement, concrete, natural and artificial stone.

It doesn't get damaged by fungi or algae.

Excellent sealing and impregnating power.

High penetration in the substrates, thus reinforcing them on their surfaces.

FIELD OF APPLICATION:

As sealing primer for concrete, lime and cement mortars, masonry, rendering, brick, etc., on façades and inside and outside walls.

SURFACE CONDITIONING:

Surfaces should be free from grease, oil, loose particles, dust or any other pollutant. The substrate could be slightly damp but it should never have pools.

METHOD OF USE:

Stir the contents in the containers before applying. Apply the primer after diluting with water in a 1:1 proportion, covering the whole surface. When applying silicate based paint in dark colors, the primer can be used mixed with water and with the paint in a 1:1:1 proportion, in order to control even more the absorption.

Twenty four hours after applying, the paint can be applied.

SPECIAL RECOMMENDATIONS:

- Never apply with temperatures below 10 °C or with relative humidity above 85%.
- Protect surfaces such as glass, anodized and lacquered aluminum, glazed surfaces, etc.

PACKAGING AND STORAGE:

TECMASIL PRIMER is supplied in 10 and 25 liter plastic containers. The product should be stored in a cool place, always protected from frost.

ED.2002/1